

# SINGER®

## INSTANT SHOWER HEATERS-WITH PRESSURE PUMP 3.5kW, 220 V

Model No: SWH-SLIM228EP



### Price:

---

~~MVR 2,524~~ MVR 2,398. (Valid for 7 days from the date this brochure is downloaded. Prices are subject to change without prior notice. For the latest pricing, always refer to our official website <https://singer.mv>)

### Warranty:

---

3 Months(s) manufacturer warranty.  
3 Months Manufacturer Warranty

## **Delivery:**

---

Delivery - Within 3 Working Days.

- Delivery Within 3 Working Days

## **Specifications:**

---

- Type: Water Heater (With Pressure Pump)
- Spray Patterns: 5 Spray Patterns (Massage, Mixed, Standard, Soothe, Jumbo)
- Water Flow Rate: 2 Liters Per Minute
- Pressure Rating: Min 0.1 Bar - Max 6 Bar
- Standards: Thailand, Canada, USA, Malaysia & Singapore Safety Standards, High Quality UK Technology Heating Element With UL Approved Standard
- Temperature Controls: Electronic Variable Power Temperature Control
- Power: 220~240V
- Safety / Protection: Triple Safety Protection (Built-In Auto Flow Switch Prevents Over Heating, Built-In 15mA Sensitivity Electric ELCB, Anti-Scalding Thermal Safety Design), Built-In Lightning Surge Protector (ELCB), Built-In RCD Residual Current Device (Cut Off Power In The Event Of Current Leakage), Plastic Stop Valve And Non-Conductive PVC Flexible Hose ( Safest & Simplest Solution In Preventing Electrocution To End User), Dual Temperature Thermal Cut-Off Protector
- Inlet / Outlet Water Connectors: 15mm (1/2" BSP)
- Special Features: Stepless Electronic Power Control, RoHS Compliance Product Free From Lead, Mercury, Cadmium, Hexavalent Chromium, Pbb And Pbde, AC Booster Pump 120W 220V
- Made In: Malaysia
- Package Contents: Shower Unit, Multi-Spray Hand Shower, Slider Rail Set, Hose & Washer, Soap Tray, Stop Valve With Filters, Screw & Wall Plugs, Operation Manual, Warranty Card
- Colors: Silver
- Dimensions: 360(H) x 240(W) x 84(D)
- Weight: 3.9 Kg
- Other Information: Ultra Slim Design, Electronic Variable Power Temperature Control, 3 In 1 Compact Stop, Flow & Filter Valve, 55 Celsius Degrees Anti-Scalding

Date: 2026-02-11 14:22